

DIREKT START ***DSE***

**2010-2011
PRODUCTS**



AutoMobility Distribution Inc.

400 Wright, St-Laurent, QC—H4N 1M6

Tel.: (514) 745-8030 Toll Free: (888) 557-8278 Fax: (514) 745-6068

www.automob.ca

DIREKT START DSE

501+



FEATURES

501AMTX5C2

Sliding door



501AM421C2

New Slim Remotes

Sliding door



501AMCHR2



- ◆ Compatible with Manual and Automatic Transmission
- ◆ Range of 2,000' / 600 m*
- ◆ Antenna with built-in white LED (Xenon style)
- ◆ Alarm function with PANIC
- ◆ Smart Tach learning with Self cranking adjustment
- ◆ Cold Start timer for 2,3 and 4 hours for 3 minutes of running time
- ◆ Dome light by-pass when remote start
- ◆ Polarity selection for parking light with relay built-in
- ◆ Programmable on-board starter kill relay to 2nd ignition, Accessory or Start
- ◆ Dedicated on demand Smart button for Silent lock and unlock
- ◆ Accept up to 3 transmitters with Easy-Write-Off for lost transmitter
- ◆ On-board and pre-wired starter kill relay
- ◆ Anti-Grind function
- ◆ Door re-lock when remote start programmable
- ◆ Door lock output negative, positive ** and reversal polarity**
- ◆ Installation diagnostic mode

*May vary depending on area, weather and / or various factors ** Requires extra part (s)

DIREKT START DSE

503



FEATURES

503AM421C2

*Sliding
door*

New Slim Remotes



503AMCHR2



503FMLEDCHR



- ♦ AM / FM One way or Two Way
- ♦ Range of 2,000' / 600 m (AM), 3,000' / 900 m (FM)*
- ♦ Antenna with built-in white LED (Xenon style)
- ♦ Featured alarm function including last door arming (LDA)
- ♦ Data port RS-232 for easy plug-in iDataLink or Fortin bypass module
- ♦ Wireless capability via GSM port
- ♦ Easy trouble shooting with memory for the last 6 events
- ♦ Three (3) programmable auxiliary outputs
- ♦ Selectable Valet and Override mode through ignition or foot brake
- ♦ Safe start with 3 different settings on the transmitter
- ♦ Four (4) different exit modes for manual transmission vehicle
- ♦ Compatible with Manual and Automatic Transmission
- ♦ Gas, Diesel and Turbo engine
- ♦ Smart Tach Learning with self cranking adjustment
- ♦ Cold Start timer for 2, 3 and 4 hours with selectable running time
- ♦ Dome light by-pass when remote start
- ♦ Polarity selection for parking light with relay built-in
- ♦ Programmable on-board starter kill relay to 2nd Ignition, Accessory or Start
- ♦ Passkey output programmable to 3rd Ignition or 3rd Start negative output
- ♦ Dedicated Smart button for Silent lock and unlock
- ♦ Accept up to 3 transmitters with Easy-Write-Off for lost transmitter
- ♦ On-board and pre-wired starter kill relay
- ♦ Anti-Grind function
- ♦ Door re-lock when remote start programmable
- ♦ Door lock output negative, positive ** and reversal polarity **
- ♦ Installation diagnostic mode

*May vary depending on area, weather and / or various factors

**Requires extra part (s)

DIREKT START DSE

503



FEATURES

503FMLCDCHR



503FMLED2



503FMLCD2



- ♦ AM / FM One way or Two Way
- ♦ Range of 2,000' / 600 m (AM), 3,000' / 900 m (FM)*
- ♦ Antenna with built-in white LED (Xenon style)
- ♦ Featured alarm function including last door arming (LDA)
- ♦ Data port RS-232 for easy plug-in iDatalink or Fortin bypass module
- ♦ Wireless capability via GSM port
- ♦ Easy trouble shooting with memory for the last 6 events
- ♦ Three (3) programmable auxiliary outputs
- ♦ Selectable Valet and Override mode through ignition or foot brake
- ♦ Safe start with 3 different settings on the transmitter
- ♦ Four (4) different exit modes for manual transmission vehicle
- ♦ Compatible with Manual and Automatic Transmission
- ♦ Gas, Diesel and Turbo engine
- ♦ Smart Tach Learning with self cranking adjustment
- ♦ Cold Start timer for 2, 3 and 4 hours with selectable running time
- ♦ Dome light by-pass when remote start
- ♦ Polarity selection for parking light with relay built-in
- ♦ Programmable on-board starter kill relay to 2nd Ignition, Accessory or Start
- ♦ Passkey output programmable to 3rd Ignition or 3rd Start negative output
- ♦ Dedicated Smart button for Silent lock and unlock
- ♦ Accept up to 3 transmitters with Easy-Write-Off for lost transmitter
- ♦ On-board and pre-wired starter kill relay
- ♦ Anti-Grind function
- ♦ Door re-lock when remote start programmable
- ♦ Door lock output negative, positive ** and reversal polarity **
- ♦ Installation diagnostic mode

*May vary depending on area, weather and / or various factors

**Requires extra part (s)

DIREKT START DSE

iSTART



FEATURES

ISTARAMTX5C2



Sliding door

ISTARAM421C2



Sliding door New Slim Remotes

ISTARAMCHR2



ISTARFMLEDCHR



- ◆ Blade web-based integration solution
- ◆ Range of 2,000' / 600 m (AM), 3,000' / 900 m (FM)*
- ◆ Antenna with built-in white LED (Xenon style)
- ◆ Remote starter firmware updateable online
- ◆ Online Programming multiple options before Installation
- ◆ AM/FM One-Way or Two-Way
- ◆ Compatible with automatic, manual transmission, gas, diesel & hybrid including "Push to Start"
- ◆ Data Port RS-232 for other external bypass module
- ◆ Wireless capability via GSM port
- ◆ Temperature sensor for cold start under -20C or -25C**
- ◆ Cold Start timer for 2, 3 and 4 hours with selectable running time
- ◆ Full Feature alarm function with True Secure Patented Dual Zone Shock Sensor**
- ◆ Automobile mini fuse type (4) on board for more safety and protection
- ◆ Easy trouble shooting with memory for the last 6 events
- ◆ Selectable Valet and Override mode through ignition or foot brake
- ◆ Safe start with 3 different settings on the transmitter
- ◆ Four (4) different exit modes for manual transmission vehicle
- ◆ Smart Tach Learning with Self cranking adjustment
- ◆ Dome light by-pass when remote start
- ◆ Polarity selection for parking light with relay built-in
- ◆ Programmable on-board starter kill relay to 2nd ignition, Accessory or Start
- ◆ Passkey output programmable to 3rd ignition or 3rd Start negative output
- ◆ Dedicated Smart button for Silent lock and unlock
- ◆ Accept up to 3 transmitters with Easy-Write-Off for lost transmitter
- ◆ On-board and pre-wired starter kill relay
- ◆ Anti-grind function
- ◆ Door re-lock when remote start programmable
- ◆ Door lock output negative, positive**and reversal polarity**
- ◆ Installation diagnostic mode

*May vary depending on area, weather and / or various factors

**Requires extra part (s)

DIREKT START DSE

iSTART



ISTARFMLCDCHR



ISTARFMLED2



ISTARFMLCD2



FEATURES

- ◆ Blade web-based integration solution
- ◆ Range of 2,000' / 600 m (AM), 3,000' / 900 m (FM)*
- ◆ Antenna with built-in white LED (Xenon style)
- ◆ Remote starter firmware updateable online
- ◆ Online Programming multiple options before Installation
- ◆ AM/FM One-Way or Two-Way
- ◆ Compatible with automatic, manual transmission, gas, diesel & hybrid including "Push to Start"
- ◆ Data Port RS-232 for other external bypass module
- ◆ Wireless capability via GSM port
- ◆ Temperature sensor for cold start under -20C or -25C**
- ◆ Cold Start timer for 2, 3 and 4 hours with selectable running time
- ◆ Full Feature alarm function with True Secure Patented Dual Zone Shock Sensor**
- ◆ Automobile mini fuse type (4) on board for more safety and protection
- ◆ Easy trouble shooting with memory for the last 6 events
- ◆ Selectable Valet and Override mode through ignition or foot brake
- ◆ Safe start with 3 different settings on the transmitter
- ◆ Four (4) different exit modes for manual transmission vehicle
- ◆ Smart Tach Learning with Self cranking adjustment
- ◆ Dome light by-pass when remote start
- ◆ Polarity selection for parking light with relay built-in
- ◆ Programmable on-board starter kill relay to 2nd ignition, Accessory or Start
- ◆ Passkey output programmable to 3rd ignition or 3rd Start negative output
- ◆ Dedicated Smart button for Silent lock and unlock
- ◆ Accept up to 3 transmitters with Easy-Write-Off for lost transmitter
- ◆ On-board and pre-wired starter kill relay
- ◆ Anti-grind function
- ◆ Door re-lock when remote start programmable
- ◆ Door lock output negative, positive**and reversal polarity**
- ◆ Installation diagnostic mode

*May vary depending on area, weather and / or various factors

**Requires extra part (s)

DIREKT START DSE

REMOTES



TX5FCN

5 Button AM Carbon Fiber remote with sliding door (340 Mhz)



TX421C

New Slim 4-Button AM Carbon Fiber Remote with Sliding door (421 Mhz)



TXAMCHR

4-Button AM Chrome Remote (340 Mhz)



TXFMCHR

4-Button FM Chrome Remote



TXFMLED

Two way FM LED remote.



TXFMLCD

Two way FM LCD remote.


Features: Vibrating mode, clock, automatic self display parking timer when door locked and keypad lock for more safety, user programmable time-start.

ACCESSORIES



MRE/MSO

Mini Relay / Mini Socket



S-MER

Mercury Switch



SS2Z.8 (for 800+)

SS2Z.i (for iStart)

Mini Shock sensor


TEMPSEN25C

Temperature sensor for Cold Start (under -20C-25C)



SIR

Siren



ANTAM1WLED

Antenna with built-in LED (340 Mhz) for models: 501AMTX5C2, 501AMCHR2, 503AMCHR2, ISTARAMTX5C2, ISTARAMCHR2



ANTAM1W421LED

Antenna with built-in LED (421 Mhz) for models: 501AM421C2, 503AM421C2, ISTARAM421C2



ANTFM2WLED

FM Antenna with built-in LED for models: 503FMLCDCHR, 503FMLCD2, ISTARFMLCDCHR, ISTARFMLCD2