## PREMIER DEFENSE





Pricelist 2011-2012

EXCLUSIVE FOR NEW CAR DEALERS!


# PREMIER DEFENSE Intelligent Mobile Security

### Premier Defense Remote Starter and Security Systems



All remote starter systems are all-in-one manual/automatic transmission and feature: - Virtual Tach System (automatic transmission only) - Tech Tool compatible - Dual 12 volt power wires - High-current outputs for Ignition, Accessory and Start - Configurable High-Current Output for 2nd Ignition, 2nd Accessory, or 2nd Start - Multi-Speed Tachometer Learning - Normal and High Tach Jumper - Gas or Diesel engine compatible - Nonvolatile system state memory - iDatalink & Xpresskit compatible - Pager Compatible - Two-way communication on RS-232 Port, INV-200 Port, Configurable engine run time (3, 15, 25 minutes -in gas mode) - Turbo mode - Idle Mode - Cold Weather Mode - Negative Hood Trigger Input - Tachometer Input - Positive Glow-plug Input - Auxiliary (-) Ground Output when Running - Independent arm/disarm outputs for factory alarm control - Hybrid vehicle mode (automatic transmission vehicles only) & PTS (Push to Start) Compatible - Limited Lifetime Warranty NEW! (-) Ignition/Accessory/Start Programmable Outputs - Disarm feature with ignition, accessory and ground out when running - Parking Light Selectable Polarity Output - Programmable Manual Transmission Ready Mode Sequence - PTS (Push to Start) Programmable Take Over Time

Options: Keyless Entry Outputs - Ignition-controlled door locks - Secure Lock - Trunk Release Output - Anti-theft Starter-Kill Output - Passive or active starter-kill arming - Arm & Disarm OEM alarm - OEM horn control - Parking lights flash/diagnostics



### PREMIER DEFENSE

### Intelligent Mobile Security

### Premier Defense Remote Starter and Security Systems



Alarm Common Features: Passive or active alarm arming - Programmable 2-stage Disarm - Temporary/Permanent Chirp Delete - Selectable siren or horn confirmation - Adjustable siren/horn pulse duration - Siren and/or horn notification of zone intrusion - LED notification of zone intrusion - Panic Mode/car finder - Remote controlled Valet Mode - Ignition controlled Valet Mode - Push-button controlled Valet Mode - Plug-in Dual stage shock sensor - 128dB 6 tone siren - Zone intrusion monitoring with zone bypass - Ignition monitoring - Door monitoring - Trunk monitoring - Hood monitoring

2-way combo alarm starter system						
PD870TW-FM	<b>t</b> → FM	(1715)				
	ĝA <mark>M</mark> .√√TS. (	HOR	6-button FM LCD transmitter chargeable via USB - Companion FM 5-button transmitter - Up to 3500ft / 1070m of range - 2-Way communication with HDX Technology - Monopole antenna with embedded bright blue LED - Status via 6 alphanumeric characters and icon LCD transmitter display - Bright backlit Liquid Crystal Display (LCD) - 8 User-programmable LCD backlight colors - Signa reception/operation confirmation (beep/text) - Alarm notification paging by custom chime or vibrate mode - User-programmable time start - User-programmable transmitter language (English/French) - User-programmable transmitter keypad lock - User-programmable 6th button (Temp, Stop, Aux, Panic, Cold Weather mode) - Passenger compartment temperature display via transmitter - Transmitter battery level indicator - On-screen ready mode on/off indicator (manual transmission models only) - On-screen engine running countdown timer - Clock with alarm function - Parking meter countdown - Remote control locator -			
# @ @ @ @ @ @ @ @ @ @ @ @ @ @ @ @ @ @ @			Temperature sensor compatible* - Multi-level shift button - Channel expander compatible* (*may require additional part(s) and/or labour)			





By default in manual transmission but can be changed very easily at the moment of installation into an automatic transmission unit



One Way

Two Way

One Way System



Two way system



FM Technology



AM Technology



Alarm System Includes full feature alarm system



Built-in, OEM-style alarm

Uses the door and hood switches along with ignition sense as alarm triggers; if tripped, the factory horn will act as an audible



Virtual Tach System combines the latest microcontroller technology and a complex algorithm. VTS is able to effectively monitor the engine starting sequence and release the starter at the right time without physically connecting the tach wire to the remote starter. The VTS constantly monitors the data and readjusts itself automatically in order to maximize its capability to start the engine properly in any weather or deteriorating battery condition.



Virtual Tach System

**HDX Technology** 

Featured on all TW systems. This technology allows the transceiver to send and receive data at the same time, almost like a full duplex system. This translates into getting the maximum range from the RF systems with much faster confirmation than any other two-way systems on the market.



HDR Technology

HDR stands for High Data Rate - one of the most advanced transmitter coding systems ever. By increasing the speed of which the data is modulated on the carrier from the remote control, short but powerful bursts of information can be transmitted.



Combine starter with Smart Start unit, download the Smart start application and enjoy all the features that Smart Start has to offer Smart Start Compatible (see Smart Start pricelist for full feature list).

# PREMIER DEFENSE Intelligent Mobile Security

ANTENNAS					
Model	Description		For use with		
ANT-SH1	SH-1	Superheterodyne dipole antenna (303 Mhz) - 3 pin	PD2.5SH, PD2.5M SH, PD3SHv2, PD3MSHv2		
ANT-SH433M	all the second s	Superheterodyne monopole antenna 433 mhz w/blue LED (SH433-101 embeded on antenna) - 4 pin	PD2.5iSH, PD2.5iM SH-433, PD2.7, PD3SH-433, PD3M SH-433		
SH433-120		Superheterodyne HDR monopole antenna 433 mhz w/blue LED and PAB	PD2.8		
FMTW-130		Two way FM HDR monopole antenna with PAB	PD372TW-FM & PD472TW-FM		
FMTW-140	10 EM	Two way FM HDR monopole antenna	PD870TW-FM		
A001-SH000		3 pin antenna harness	White connectors on both ends= SH & R1 (1) White connector & (1) black connector = FM & AM		
A001-SH001		4 pin antenna harness			
1 WAY REMOTES					
PR-85		5 button remote 433mhz HDR (blue LED)	PD2.8		
PR-5	(a) (a) (b) (b) (c) (c) (c) (c) (c) (c) (c) (c) (c) (c	5 button remote 433mhz (amber LED)	PD2.7		
PR 4SH-433		4 button remote 433mhz (amber LED)	PD2.5SH (433), PD2.5MSH (433), PD3SHv.2 (433), PD3MSHv.2 (433)		
PR 4SH		4 button SH remote 303mhz (green LED)	PD2.5, PD2.5I, PD2.5M, PD3, PD3M, PD3v2, PD3Mv2, PD2.5SH, PD2.5ISH, PD2.5MSH, PD3SH, PD3SHv2, PD3MSHv2		
PR425OW		5 button one way FM HDR transmitter with multilevel shift button - mat finish/amber LED	Companion remote for PD372TW-FM and PD472TW-FM and can be used with PD870TW-FM		
PR525OW		5 button one way FM HDR transmitter with multilevel shift button - glossy finish/blue LED	PD870TW companion remote. Can also be used as a companion remote for PD372TW-FM and PD472TW-FM		

## REMIER DEFENS Intelligent Mobile Security

2 WAY REMOTES						
PR285LED	90	FM Two way LED "HDR"remote	PD372TW-FM			
PR476LCD		Two way FM Hybrid LCD remote with "HDX" & "HDR" Technologies (6 bt)	PD472TW-FM			
PR386LCD		Two way FM LCD HDR remote with "HDX" Technology (6 bt) and chargeable via USB	PD870TW-FM			

Casings available for most remotes; please contact the order department for model number, cost and availability

	-	
GSS-1	NS GLASS SEASON	Glass break sensor
Shock-500	-	Dual zone shock sensor
Siren		128dB siren
ACCESSORIES		
AS-PRG1000		Tech tool - Large, easy to read 20-character-by4-line bright blue backlit LCD - Easy connection to remote car starter unit via antenna's cable - Effortlessly programs remote starter's functions, options, tach and transmitters - Multiple user-programmable memory preset for quick programming of features/options - Quick read/write functions, perfect when swapping a unit - Built-in OBD2 code eraser- CAN ready - PC updateable for future firmware upgrades
8602T		USB charger for PR386LCD transmitter *Please note that a regular USB charger will not work*
TEMP-101	<b>\$</b>	Plug-in temperature sensor for LCD systems
MCX-100		Plug-in 5 channel expansion module with dome light supervision
INV200		Plug-in door lock polarity inverter
LEDPLUGIN		Plug-in LED (non flashing)
RLY100		30/40 amp relay
HRN500		5 wire relay socket 18"
ACTUATORS		2 deed control deed leek cristers
TL-6202 TL-6204	1	2 door central door lock system 4 door central door lock system
TT-8204		Power trunk release
11-0000	<u> </u>	1 ONOT WAIR FORGUS